

## air conditioner spec



model	HPC-5600K
cooling area	50~60m <sup>2</sup>
cooling ability	6.5kW(5600kcal/h)
power supply	AC 220v 50hz(2.2kw)
product size	W535x D670 x H1,300mm
weight	85kg
power code	plug type
refrigerant	R410A
energy consumption	2.2kw/h
operating temperature	25°C~50°C
maxium length of air ducts	12m
filter	aluminum



model	HPC-7000K
cooling area	72m <sup>2</sup>
cooling ability	8.5kW(7300kcal/h)
power supply	AC 220v 50hz(2.6kw)
product size	W535x D670 x H1300mm
weight	90kg
power code	plug type
refrigerant	R410A
energy consumption	2.6kw/h
operating temperature	25°C~50°C
maxium length of air ducts	12m
filter	aluminum



model	HPC-9000K
cooling area	94~106m <sup>2</sup>
cooling ability	11.0kW(9500kcal/h)
power supply	AC 220v 50hz(5.37kw)
product size	W740x D840 x H1400mm
weight	180kg
power code	termianal type
refrigerant	R410A
energy consumption	4.4 kw/h
operating temperature	25°C~50°C
maxium length of air ducts	12m
filter	aluminum



model	HPC-16000K
cooling area	106~156m <sup>2</sup>
cooling ability	18.6kW(16000kcal/h)
power supply	AC 220v/380v 50hz(8.5kw)
product size	W740x D1400 x H1490mm
weight	250kg
power code	termianal type
refrigerant	R410A
energy consumption	10.1 kw/h
operating temperature	25°C~50°C
maxium length of air ducts	12m
filter	aluminum